

Technical sheet :

# **GENERAL PURPOSE BUCKET**

---



## **Benefits**

- General purpose attachment for a daily use.
- Basic attachment for loading and unloading operations.
- Robust and easy to use this bucket meets the needs of very different work fields.
- Ideal bucket for handling bulk materials: sand & gravel, earth, broken glass etc.

## **Technical characteristics**

- Wide range of bucket capacity from 730 L to 1000 L.
- Recovery bucket suitable for handling materials with a density  $\leq 2,1$ .
- Reinforced structure (base, blade, sides).
- Optional "LDR" 500 HB bolt-on wear plate.
- Bucket to be used on machines equipped with an integrated side shift carriage (TSDL).

Capacities	CBR 600 / 1500	CBR 730 / 1850	CBR 780 / 1950	CBR 850 / 2100	CBR 900 / 2250	CBR 1000 / 2450	CBR 2000 / 2500 LDR MHT
Heaped Capacity (l)	583	735	778	843	904	990	-
Struck capacity (l)	484	600	663	685	736	804	-
Weight and dimensions							
Width (mm)	1500	1850	1950	2100	2250	2450	2482
Length (mm)	845	815	815	838	815	815	1418
Overall weight (kg)	274	318	328	358	360	381	926
Working Parameters							
Machine Equipment	No predisposition required	No predisposition required	No predisposition required	No predisposition required	No predisposition required	No predisposition required	-
Other Data for Attachments							
Bolted wearplate (LDR)	Not Standard	Not Standard	Not Standard	Not Standard	Not Standard	Not Standard	-
Wear plate hardness	500	500	500	500	500	500	-
Machines compatibility	CBR 600 / 1500	CBR 730 / 1850	CBR 780 / 1950	CBR 850 / 2100	CBR 900 / 2250	CBR 1000 / 2450	CBR 2000 / 2500 LDR MHT
Reference number	570614	571831	570613	653047	653749	654716	-
Reference number bolted wearplate (LDR)	52584881	52000369	-	-	-	52000370	-
Skid Steer Carriage reference	52000783	-	-	-	-	-	-
MLT 420 - 60 H	X	-	-	-	-	-	-
MLT 625 - 75 H	-	X	-	-	-	-	-
MLT-X 625 - 75 H	-	X	-	-	-	-	-
MLT-X 735 T LSU	-	-	X	-	X	-	-
MT 420 H	X	-	-	-	-	-	-
MT 625 H	-	X	-	-	-	-	-
MT 625 HA	-	X	-	-	-	-	-
MT 933 Easy	-	-	-	-	X	-	-
MT 1033 easy	-	-	-	-	X	-	-
MT 1135	-	-	-	-	X	-	-
MT 1135 H easy ST5	-	-	-	-	X	-	-
MT 1135 HA Easy ST5	-	-	-	-	X	-	-
MT 1135 easy ST5	-	-	-	-	X	-	-
MT 1440	-	-	X	-	X	-	-
MT 1440 A	-	-	X	-	X	-	-
MT 1440 HA	-	-	X	-	X	-	-
MT 1840	-	-	-	-	X	-	-
MT 1840 A	-	-	-	-	X	-	-
MT 1840 HA	-	-	-	-	X	-	-
MT-X 625 H	-	X	-	-	-	-	-
MT-X 1033	-	-	-	-	X	-	-
MT-X 1440	-	-	X	-	X	-	-
MT-X 1440 A	-	-	X	-	X	-	-
MT-X 1840	-	-	-	-	X	-	-
MT-X 1840 A	-	-	-	-	X	-	-
Reference number E-RECO	-	-	-	-	921281	921282	52000532
MHT 10130	-	-	-	-	-	-	X
MHT 10180	-	-	-	-	-	-	X
MHT 10230	-	-	-	-	-	-	X
MHT-X 10130	-	-	-	-	-	-	X
MHT-X 10180	-	-	-	-	-	-	X
MHT-X 10230	-	-	-	-	-	-	X
MRT 2150 Privilege Plus	-	-	-	-	X	-	-
MRT 2470 Privilege Plus	-	-	-	-	X	-	-
MRT 2550 Privilege Plus	-	-	-	-	X	-	-
MRT 3050 Privilege Plus	-	-	-	-	X	-	-
MRT-X 2150 Privilege Plus	-	-	-	-	X	-	-
MRT-X 2470 Privilege Plus	-	-	-	-	X	-	-
MRT-X 2550 Privilege Plus	-	-	-	-	X	-	-
MRT-X 3050 Privilege Plus	-	-	-	-	X	-	-
Reference number E-RECO 2	-	-	-	-	925903	925904	-
MRT 1640 Easy T4 S2 360°	-	-	-	-	X	-	-

Machines compatibility	CBR 600 / 1500	CBR 730 / 1850	CBR 780 / 1950	CBR 850 / 2100	CBR 900 / 2250	CBR 1000 / 2450	CBR 2000 / 2500 LDR MHT
MRT 1840 Easy T4 S2 360°	-	-	-	-	X	-	-
MRT 1840 Easy T4 S2 400°	-	-	-	-	X	-	-
MRT 2145 Easy T4 S2 360°	-	-	-	-	X	-	-
MRT 2145 Easy T4 S2 400°	-	-	-	-	X	-	-
MRT 2545 Easy T4 S2 360°	-	-	-	-	X	-	-
MRT 2545 Easy T4 S2 400°	-	-	-	-	X	-	-
MRT-X 1440 Easy 400°	-	-	-	-	X	-	-
MRT-X 1640 Easy 360°	-	-	-	-	X	-	-
MRT-X 1640 Easy 400°	-	-	-	-	X	-	-
MRT-X 1840 Easy 360°	-	-	-	-	X	-	-
MRT-X 1840 Easy 400°	-	-	-	-	X	-	-
MRT-X 2545 Easy 360°	-	-	-	-	X	-	-
MRT-X 2545 Easy 400°	-	-	-	-	X	-	-



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508  
RCS Nantes